

**3745-56-29 Special requirements for ignitable or reactive waste.**

Ignitable or reactive waste shall not be placed in a surface impoundment, unless the waste and impoundment satisfy all applicable requirements of Chapter 3745-270 of the Administrative Code, and:

- (A) The waste is treated, rendered, or mixed before or immediately after placement in the impoundment so that the resulting waste, mixture, or dissolution of material no longer meets the definition of ignitable or reactive waste under rule 3745-51-21 or 3745-51-23 of the Administrative Code and paragraph (B) of rule 3745-54-17 of the Administrative Code is complied with; or
- (B) The waste is managed in such a way that it is protected from any material or conditions which may cause it to ignite or react; or
- (C) The surface impoundment is used solely for emergencies.

[Comment: As required by rule 3745-54-13 of the Administrative Code, the waste analysis plan must include analyses needed to comply with this rule. Also, paragraph (C) of rule 3745-54-17 of the Administrative Code requires waste analyses, trial tests, or other documentation to assure compliance with paragraph (B) of rule 3745-54-17 of the Administrative Code. As required by rule 3745-54-73 of the Administrative Code, the owner or operator must place the results of each waste analysis and trial test, and any documented information, in the operating record of the facility.]

Effective: 12/07/2000  
119.032 review dates: Exempt  
Promulgated under: 119.03  
Statutory authority: 3734.12  
Rule amplifies: 3734.12  
Prior effective dates: 01/07/1983, 02/11/1992